

# Safety Data Sheet

## According to 91/155 EEC

Printing date 23.06.2009

Revision: 23.06.2009

### 1 Identification of the substance/preparation and of the company/undertaking

· **Product details**

· **Trade name:** methyl acrylate

**Manufacturer/Supplier:**

Asiatic Chemicals Pakistan



**Address**

30-Mussa Market 2nd Floor,  
Opp Sindh Madarsah  
Shahrah-e-Liaquat

**Mobile**

0092-320-4320301

**Email**

asiatic-petro@cyber.net.pk  
asiatic@asiatic.com.pk

**Tel No**

0092-21-32422537

**Fax No**

0092-21-3241554

### 2 Composition/information on ingredients

· **Chemical characterization:**

· **CAS No. Description**

96-33-3 methyl acrylate

· **Identification number(s)**

· **EINECS Number:** 202-500-6

· **Index number:** 607-034-00-0

### 3 Hazards identification

· **Hazard description:**



Xn Harmful

F Highly flammable

· **Information concerning particular hazards for human and environment:**

R 11 Highly flammable.

R 20/21/22 Harmful by inhalation, in contact with skin and if swallowed.

R 36/37/38 Irritating to eyes, respiratory system and skin.

R 43 May cause sensitisation by skin contact.

### 4 First aid measures

· **General information:**

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· **After inhalation:**

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

· **After skin contact:** Immediately wash with water and soap and rinse thoroughly.

· **After eye contact:**

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· **After swallowing:** Call for a doctor immediately.

### 5 Fire-fighting measures

· **Suitable extinguishing agents:**

CO<sub>2</sub>, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

· **For safety reasons unsuitable extinguishing agents:** Water with full jet

· **Protective equipment:** Mouth respiratory protective device.

UAE

(Contd. on page 2)

# Safety Data Sheet

## According to 91/155 EEC

Printing date 23.06.2009

Revision: 23.06.2009

Trade name: methyl acrylate

(Contd. of page 1)

### 6 Accidental release measures

- **Person-related safety precautions:** Wear protective equipment. Keep unprotected persons away.
- **Measures for environmental protection:** Do not allow to enter sewers/ surface or ground water.
- **Measures for cleaning/collecting:**  
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).  
Dispose contaminated material as waste according to item 13.  
Ensure adequate ventilation.

### 7 Handling and storage

- **Handling:**
- **Information for safe handling:** Ensure good ventilation/exhaustion at the workplace.
- **Information about fire - and explosion protection:**  
Keep ignition sources away - Do not smoke.  
Protect against electrostatic charges.
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Store in a cool location.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**  
Keep container tightly sealed.  
Store in cool, dry conditions in well sealed receptacles.

### 8 Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.

- **Ingredients with limit values that require monitoring at the workplace:**

#### 96-33-3 methyl acrylate

PEL (USA)	35 mg/m <sup>3</sup> , 10 ppm
	Skin
REL (USA)	35 mg/m <sup>3</sup> , 10 ppm
	Skin
TLV (USA)	7 mg/m <sup>3</sup> , 2 ppm
	Skin; SEN

- **Additional information:** The lists valid during the making were used as basis.
- **Personal protective equipment:**
- **General protective and hygienic measures:**  
Keep away from foodstuffs, beverages and feed.  
Immediately remove all soiled and contaminated clothing  
Wash hands before breaks and at the end of work.  
Avoid contact with the eyes and skin.
- **Respiratory protection:**  
In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.
- **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.  
Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.  
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

(Contd. on page 3)

# Safety Data Sheet

## According to 91/155 EEC

Printing date 23.06.2009

Revision: 23.06.2009

Trade name: methyl acrylate

(Contd. of page 2)

- **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

- **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- **Eye protection:**



Tightly sealed goggles

### 9 Physical and chemical properties

- **General Information**

<b>Form:</b>	Fluid
<b>Colour:</b>	Colourless
<b>Odour:</b>	Pungent

- **Change in condition**

**Melting point/Melting range:** -76.5°C  
**Boiling point/Boiling range:** 80.5°C

- **Flash point:** -3°C

- **Ignition temperature:** 415°C

- **Danger of explosion:** Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

- **Explosion limits:**

<b>Lower:</b>	2.4 Vol %
<b>Upper:</b>	18.6 Vol %

- **Vapour pressure at 20°C:** 89 hPa

- **Density at 20°C:** 0.9535 g/cm<sup>3</sup>

- **Solubility in / Miscibility with water at 20°C:** 60 g/l

### 10 Stability and reactivity

- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Dangerous reactions** No dangerous reactions known.
- **Dangerous decomposition products:** No dangerous decomposition products known.

### 11 Toxicological information

- **Acute toxicity:**

- **LD/LC50 values relevant for classification:**

Oral	LD50	277 mg/kg (rat)
Dermal	LD50	1243 mg/kg (rabbit)

- **Primary irritant effect:**

- **on the skin:** Irritant to skin and mucous membranes.
- **on the eye:** Irritating effect.

(Contd. on page 4)

# Safety Data Sheet

## According to 91/155 EEC

Printing date 23.06.2009

Revision: 23.06.2009

Trade name: methyl acrylate

(Contd. of page 3)

- **Sensitization:** Sensitization possible through skin contact.

### 12 Ecological information

- **General notes:**

Water hazard class 2 (German Regulation) (Assessment by list): hazardous for water  
Do not allow product to reach ground water, water course or sewage system.  
Danger to drinking water if even small quantities leak into the ground.

### 13 Disposal considerations

- **Product:**

- **Recommendation**

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- **Uncleaned packaging:**

- **Recommendation:** Disposal must be made according to official regulations.

### 14 Transport information

- **Land transport ADR/RID (cross-border)**



- **ADR/RID class:** 3 Flammable liquids.
- **Danger code (Kemler):** 339
- **UN-Number:** 1919
- **Packaging group:** II
- **Hazard label:** 3
- **Description of goods:** 1919 METHYL ACRYLATE, STABILIZED

- **Maritime transport IMDG:**



- **IMDG Class:** 3
- **UN Number:** 1919
- **Label:** 3
- **Packaging group:** II
- **EMS Number:** F-E,S-D
- **Marine pollutant:** No
- **Proper shipping name:** METHYL ACRYLATE, STABILIZED

- **Air transport ICAO-TI and IATA-DGR:**



- **ICAO/IATA Class:** 3
- **UN/ID Number:** 1919
- **Label:** 3
- **Packaging group:** II

(Contd. on page 5)

# Safety Data Sheet

## According to 91/155 EEC

Printing date 23.06.2009

Revision: 23.06.2009

**Trade name: methyl acrylate**

(Contd. of page 4)

**· Proper shipping name: METHYL ACRYLATE, STABILIZED**

### 15 Regulatory information

**· Labelling according to EU guidelines:**

The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials.

**· Code letter and hazard designation of product:**

Xn Harmful

F Highly flammable

**· Risk phrases:**

11 Highly flammable.

20/21/22 Harmful by inhalation, in contact with skin and if swallowed.

36/37/38 Irritating to eyes, respiratory system and skin.

43 May cause sensitisation by skin contact.

**· Safety phrases:**

2 Keep out of the reach of children.

9 Keep container in a well-ventilated place.

25 Avoid contact with eyes.

26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

### 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

**· Department issuing MSDS: Product safety department****· Contact: Mr. Menon**

UAE